

# ProTek PLUS

## Specifications

Product name:	ProTek PLUS
Floor type:	WPC Plank
Plank size:	9" x 60"
Structure:	7.5mm total thickness (5mm extruded waterproof core, 1.5mm virgin vinyl LVT top layer, 1mm IXPE pad)
Wear Layer	0.5mm (20mil)
Surface finish:	Enhanced Ceramic Bead (ECB) coating for scratch and stain resistance
Texture:	Wood Grain (11 colors), Embossed in Register (5 colors)
Edge type:	Pressed bevel
Installation:	Floating
Packaging:	6 pieces / carton 22.12 sf carton, 76 cartons per pallet 17 pallets per container, 35 lbs. per carton
Locking Mechanism:	Unilin Licensed: Unilic Angle/ Angle
Warranty:	Lifetime Residential 10 Year Light-Commercial

TEST	DESCRIPTION	REQUIREMENT	RESULT
ASTM D6111-13a	Density	>0.8g/cm <sup>3</sup>	PASS
ASTM E648-19a	Critical Radiant Flux Smoke Density Flaming and Non Flaming	Class 1: >0.45W/cm <sup>2</sup>	PASS
ASTM C1208-07	Static Friction Coefficient	>0.6 (dry and wet)	PASS
ASTM F970-17	Static Load Limit	<0.005" @ 250 psi.	PASS
ASTM F1914-07	Residual Indentation	≤ 8% average., ≤ 10% max.	PASS
NALFA 3.9	Castor Chair	>25,000 cycles	PASS
ASTM D4060	Abrasion Test	>5000 cycles	PASS No puncture to the wear-or décor layer.
NALFA LF-01	Large Ball Impact Resistance	Drop Height: 1000mm	PASS No cracking or fracture
NALFA 3.2	Thickness Swell	</=12%	PASS
ASTM F1514-19	Resistance to Heat	ΔE < 8.0 Max	PASS
ASTM F1515-21	Resistance to Light	ΔE < 8.0 Max	PASS

SOUND TESTING	ASTM E492	ASTM E2179	ASTM E90	The International Building Code (IBC) mandates a minimum requirement for both STC and IIC of 50
6" Concrete Slab Slab	IIC = 68 *	ΔIIC = 23*	STC= 68	

\* with Drop Ceiling

CERTIFICATIONS	FLOORSCORE and GREENGUARD GOLD
----------------	--------------------------------

July 22, 2025

